

## Metals Kingdom Industry Limited

Tel: +86-312-3182007 Mobile: 13930205358 Fax:+ 86-312-3182003

Web: <a href="http://www.sincereunion.com">http://www.sincereunion.com</a> <a href="www.metalskingdom.com">www.metalskingdom.com</a> <a href="mailto:sales@sincereunion.com">Email: sales@sincereunion.com</a> <a href="mailto:sales@metalskingdom.com">sales@metalskingdom.com</a> <a href="mailto:Add">Add: 1131, Hengtong Fortune Center, 709 Chaoyang North Street</a>,

New Tech Development Zone, Baoding City, Hebei, P.R. China PC071000

# **Material Safety Data Sheet**

# ZINC CARBONATE

## 1. Product Identification

**Synonyms:** Basic zinc carbonate; zinc subcarbonate; carbonic acid, zinc salt (1:1)

**CAS No.:** 5970-47-8

**Molecular Weight:** Not applicable to mixtures. **Chemical Formula:** ZnCO3• 2Zn(OH)2•H2O

Manufacturer: Metals Kingdom Industry Limited

Address: 1131, Hengtong Fortune Center, 709 Chaoyang North Street

New Tech Development Zone, Baoding City, Hebei, P.R. China PC071000

Tel:+ 86-312-3182007 Mobile: +86-18903120772 Fax:+ 86-312-3182003 Email: sales@sincereunion.com sales@metalskingdom.com

## 2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Zinc Carbonate	3486-35-9	ca. 3%	Yes

## 3. Hazards Identification

Emergency (	U	verview

-----

CAUTION! MAY BE HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. MAY CAUSE IRRITATION TO SKIN, EYES, AND RESPIRATORY TRACT.

**J.T. Baker SAF-T-DATA**<sup>(tm)</sup> Ratings (Provided here for your convenience)

\_\_\_\_\_\_

Health Rating: 1 - Slight

Flammability Rating: 1 - Slight Reactivity Rating: 0 - None Contact Rating: 1 - Slight

Lab Protective Equip: GOGGLES; LAB COAT



## Metals Kingdom Industry Limited

Tel: +86-312-3182007 Mobile: 13930205358 Fax:+ 86-312-3182003

Web: <a href="http://www.sincereunion.com">http://www.sincereunion.com</a> <a href="www.metalskingdom.com">www.metalskingdom.com</a> <a href="mailto:sales@sincereunion.com">Email: sales@sincereunion.com</a> <a href="mailto:sales@sincereunion.com">sales@metalskingdom.com</a> <a href="mailto:Add">Add: 1131, Hengtong Fortune Center, 709 Chaoyang North Street,">Chaoyang North Street,</a>

New Tech Development Zone, Baoding City, Hebei, P.R. China PC071000

Storage Color Code: Orange (General Storage)

\_\_\_\_\_

#### **Potential Health Effects**

\_\_\_\_\_

#### **Inhalation:**

Zinc carbonate can irritate the respiratory tract, the effect being that of a mild alkali. Some soreness and coughing are symptoms.

#### **Ingestion:**

Not considered a significantly toxic substance, but contact with gastric juice can produce zinc chloride. Pain and strictures or cramps may occur in this case, and medical attention should be obtained.

#### **Skin Contact:**

Mild irritant and astringent, can cause pain and redness on long contact.

## **Eye Contact:**

Mild, alkaline irritant, may cause some mechanical injury.

#### **Chronic Exposure:**

No information found.

## **Aggravation of Pre-existing Conditions:**

No information found.

## 4. First Aid Measures

## **Inhalation:**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

#### **Ingestion:**

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person.

### **Skin Contact:**

Wash exposed area with soap and water. Get medical advice if irritation develops.

#### **Eye Contact:**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Call a physician if irritation persists.

## 5. Fire Fighting Measures

#### Fire:

Not considered to be a fire hazard. Sealed containers may burst under fire conditions due to release of carbon dioxide.

## **Explosion:**



## Metals Kingdom Industry Limited

Tel: +86-312-3182007 Mobile: 13930205358 Fax:+ 86-312-3182003

Web: <a href="http://www.sincereunion.com">http://www.sincereunion.com</a> <a href="www.metalskingdom.com">www.metalskingdom.com</a> <a href="mailto:sales@sincereunion.com">Email: sales@sincereunion.com</a> <a href="mailto:sales@metalskingdom.com">sales@metalskingdom.com</a> <a href="mailto:Add: 1131, Hengtong Fortune Center">Add: 1131, Hengtong Fortune Center</a>, 709 Chaoyang North Street,

New Tech Development Zone, Baoding City, Hebei, P.R. China PC071000

Not considered to be an explosion hazard.

## Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire.

## **Special Information:**

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

## 6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

## 7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

# 8. Exposure Controls/Personal Protection

-OSHA Permissible Exposure Limit (PEL):

fume: 5 mg/m3 (TWA)

respirable fraction: 5 mg/m3 (TWA) total dusts: 15 mg/m3 (TWA)

-ACGIH Threshold Limit Value (TLV):

2 mg/m3 (TWA), 10 mg/m3 (STEL), Respirable fraction

## **Ventilation System:**

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

## **Personal Respirators (NIOSH Approved):**

If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest.. A full-face



## Metals Kingdom Industry Limited

Tel: +86-312-3182007 Mobile: 13930205358 Fax:+ 86-312-3182003

Web: <a href="http://www.sincereunion.com">http://www.sincereunion.com</a> <a href="www.metalskingdom.com">www.metalskingdom.com</a> <a href="mailto:sales@sincereunion.com">Email: sales@sincereunion.com</a> <a href="mailto:sales@sincereunion.com">sales@metalskingdom.com</a> <a href="mailto:Add: 1131, Hengtong Fortune Center">Add: 1131, Hengtong Fortune Center</a>, 709 Chaoyang North Street,

New Tech Development Zone, Baoding City, Hebei, P.R. China PC071000

piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

## **Skin Protection:**

Wear protective gloves and clean body-covering clothing.

### **Eye Protection:**

Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

## 9. Physical and Chemical Properties

Appearance: White powder.

Odor: Odorless.

Solubility: Insoluble in water.

Density: 4.4

**pH:** No information found.

% Volatiles by volume @ 21C (70F): 0

**Boiling Point:** Not applicable.

**Melting Point:** 

Vapor Density (Air=1): No information found.

Vapor Pressure (mm Hg): No information found.

Evaporation Rate (BuAc=1): No information found.

## 10. Stability and Reactivity

## **Stability:**

Stable under ordinary conditions of use and storage.

## **Hazardous Decomposition Products:**

Fumes of zinc oxide can form at high temperatures.

## **Hazardous Polymerization:**

Will not occur.

#### **Incompatibilities:**

May react explosively with chlorinated rubber or magnesium at elevated temperatures.

## Conditions to Avoid:

Incompatibles.



# Metals Kingdom Industry Limited

Tel: +86-312-3182007 Mobile: 13930205358 Fax:+ 86-312-3182003

Web: <a href="http://www.sincereunion.com">http://www.sincereunion.com</a> <a href="www.metalskingdom.com">www.metalskingdom.com</a> <a href="mailto:sales@sincereunion.com">Email: sales@sincereunion.com</a> <a href="mailto:sales@sincereunion.com">sales@metalskingdom.com</a> <a href="mailto:sales@sincereunion.com">sales@sincereunion.com</a> <a href="mailto:sales@s

Add: 1131, Hengtong Fortune Center, 709 Chaoyang North Street,

New Tech Development Zone, Baoding City, Hebei, P.R. China PC071000

# 11. Toxicological Information



## Metals Kingdom Industry Limited

Tel: +86-312-3182007 Mobile: 13930205358 Fax:+ 86-312-3182003

Web: <a href="http://www.sincereunion.com">http://www.sincereunion.com</a> <a href="http://www.metalskingdom.com">www.metalskingdom.com</a> <a href="mailto:sales@sincereunion.com">Email: sales@sincereunion.com</a> <a href="mailto:sales@sincereunion.com">sales@metalskingdom.com</a> <a href="mailto:Add: 1131, Hengtong Fortune Center">Add: 1131, Hengtong Fortune Center</a>, 709 Chaoyang North Street,

New Tech Development Zone, Baoding City, Hebei, P.R. China PC071000

Zinc Carbonate (3486-35-9)		Yes	Yes	No Yes
\Federal, State & International Re	egulati	ons –	Part 1\	
	-SARA	302-		SARA 313
Ingredient	RQ	TPQ	List	Chemical Catg.
Zinc Carbonate (3486-35-9)	No	No	No	Zinc compoun
\Federal, State & International Re	egulati	ons -	Part 2\	
			-RCRA-	-TSCA-
Ingredient	CERCL	A	261. 33	8 (d)
Zinc Carbonate (3486-35-9)	1000	_	No	No
Chemical Weapons Convention: No TSCA	12(b):	No	CDTA:	No
ARA 311/312: Acute: Yes Chronic: No	Fire:	No F	ressure	: No
Reactivity: No (Mixture / Solid)				

Australian Hazchem Code: None allocated.

Poison Schedule: None allocated.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

## 16. Other Information

NFPA Ratings: Health: 1 Flammability: 0 Reactivity: 0

**Label Hazard Warning:** 

CAUTION! MAY BE HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. MAY CAUSE IRRITATION TO SKIN, EYES, AND RESPIRATORY TRACT.

## **Label Precautions:**

Avoid breathing dust.

Keep container closed.

Use with adequate ventilation.

Wash thoroughly after handling.

## **Label First Aid:**

If inhaled, remove to fresh air. Get medical attention for any breathing difficulty. In case of contact, immediately flush



## Metals Kingdom Industry Limited

Tel: +86-312-3182007 Mobile: 13930205358 Fax:+ 86-312-3182003

Web: <a href="http://www.sincereunion.com">http://www.sincereunion.com</a> <a href="www.metalskingdom.com">www.metalskingdom.com</a> <a href="mailto:sales@sincereunion.com">Email: sales@sincereunion.com</a> <a href="mailto:sales@sincereunion.com">sales@metalskingdom.com</a> <a href="mailto:Add">Add: 1131, Hengtong Fortune Center, 709 Chaoyang North Street,">Chaoyang North Street,</a>

New Tech Development Zone, Baoding City, Hebei, P.R. China PC071000

eyes or skin with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists. If swallowed, give large amounts of water to drink. Never give anything by mouth to an unconscious person.

#### **Product Use:**

Laboratory Reagent.

**Revision Information:** No Changes.

#### **Disclaimer:**

\*

**Metals Kindom Industry Limited** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.

Metals Kindom Industry Limited MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, Metals Kindom Industry Limited WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

\*\*\*\*\*\*\*\*\*\*\*