



Shenzhen Kanglibang Science and Technology Co., Ltd.
Material Safety Data Sheet

Page No.: 1/5
Last Revision Date: 2012/04/01

SILICONE ADHESIVE

1. COMMODITY AND INTRODUCTION OF SUPPLIER

Product Name: SILICONE ADHESIVE

Product Code: CL-24S-2

Manufacturer/Supplier: *Shenzhen Kanglibang Science and Technology Co., Ltd.*

ADD: H Blg,Xinwei 3rd Industrial Area, Dalang Street, Longhua Town, Baoan District, Shenzhen City,
Guandong Province, China.

Tel:0755- 81478876 & 81478875

Fax: 0755-81478372

Email Address:export@klbsilicone.com

Emergency Telephone/Fax Number: 0755-81478372

2. COMPOSITION / INFORMATION ON INGREDIENTS

Pure Substance:

English Name: Organosilicone Cross-linking Agent, Alcohols Solvent, Hydroxide Radical Cellulose,
Different Siloxane Polymer

Chemical Name:

CAS No.: CH₃OH, C₆H₅CH₃, CMC

Percentage for Chemical Ingredient: None

3. HAZARD IDENTIFICATION

Important Symptoms And Hazard Effects:

Hazard Effects: Not hazardous

Environment Effects: None

Hazard Classification: Not hazardous

Specific Hazards: None

Cardinal Symptoms:



The steam are irritating to eyes and respiratory system and excess smell will cause nonallergic asthma.

Hazard Classification: Not hazardous

4. FIRST AID MEASURES

First Aid Measures :

Inhalation: Move to the open place for breathing fresh air, no breathe should make breathing, Oxygen therapy if dyspnea

Skin: Washing with soap.

Eyes: Immediately flush with plenty of water.

Oral: Get medical attention.

Comments: Treat symptomatically.

Important Symptoms And Hazard Effects: None

Personal Protection for First Aid or Rescue Personnel: Conventional treatment.

Note to physicians: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

On large fires use AFFF alcohol compatible foam or water spray (fog). On small fires use carbon dioxide(CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.

Specific Potential Hazards: It won't be burning, unless contact fire

Special Fire Fighting Procedures: None

Special protective equipment for the Fire Fighters: Self-contained firefighter uniform.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wearing gloves, Handle gently, Avoid pollution.

Environmental Precautions: Sealing after using.

Methods for Cleaning up: It can be cleaned by kerosene, gas and toluene.



Shenzhen Kanglibang Science and Technology Co., Ltd.

Material Safety Data Sheet

Last Revision Date: 2012/04/01

7. HANDLING AND STORAGE

Handling Precautions: sealing.

Storage Conditions: Keep in cool and ventilated place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: None special protecting measures should be needed. Wearing gloves for avoiding pollution.

Controls Parameter: None

Biological indicators: None

Personal Protective Equipment:

Respiratory protection: Disposable mask

Hand protection: Gloves

Eye protection: None should be needed.

Skin protection: None should be needed.

Hygiene Measures: None special protecting measures should be needed. Wearing gloves for avoiding pollution.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| Material Status: : Liquid | Physical Form: Water |
| Color : Transparent | Odor: Some odor |
| pH : Not determined | Boiling point/range: 65~130°C |
| Decomposition temperature: 45-150°C | Flash Point: 3.3°C |
| | Testing Method: ASTM M429-B |
| Autoignition temperature: Not determined. | Explosive Limit: Not determined. |
| Vapor Pressure: Not determined. | Vapour Density (air=1): Not determined. |
| Density :0.85 | Water Solubility: 100% |

10. STABILITY AND REACTIVITY



Shenzhen Kanglibang Science and Technology Co., Ltd.
Material Safety Data Sheet

Stability: Stable at room temperature.

Possibility of Hazardous Reactions: Will occur cross-linking reaction while heating, irradiating and peroxidizing. Will occur burning while firing and depolymerizing with acid and alkali.

Conditions to Avoid: Away from heat and open flame.

Materials to Avoid: Fire, water, acid, alkali and peroxide.

Hazardous Decomposition Products: None

Page No.: 4/5

Last Revision Date: 2012/04/01

11. TOXICOLOGICAL INFORMATION

Acute Toxicity: None

Part affect: None

Sensitive: None

Chronic Toxicity : None.

Other Health Hazard Information: None.

12. ECOLOGICAL INFORMATION

Probably Environmental Effects/ Mobility in Soil: It has good degradation property resistance of microorganism, but it also can be degraded to Silicon dioxide and Carbon oxides by photolysis after degrading to micromolecule by acid and alkali in the soil mixing into the soil and air.

13. DISPOSAL CONSIDERATIONS

Product Disposal: Dispose of in accordance with local regulations.



Shenzhen Kanglibang Science and Technology Co., Ltd.
Material Safety Data Sheet

Page No.: 5/5
Last Revision Date: 2012/04/01

14. TRANSPORT INFORMATION

International Transportation: None.

UN number: None.

Transportation in China: According with liquid transportation method.

Special Requirements and Additional Information: According with liquid transportation method.

15. REGULATORY INFORMATION TRANSPORT INFORMATION

Applicable Laws: ROHS.

16. OTHER INFORMATION

References:

Prepared by: *Shenzhen Kanglibang Science and Technology Co., Ltd.*

First Issuing Date: 2012-4-1

Tel: 0755-81478876 81478875

This information is offered in good faith as typical values and not as a product specification. No warranty, expressed or implied, is hereby made. Each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

Shenzhen Kanglibang Science and Technology Co., Ltd.