

■ ATER TREAT TM wohingwater.com Tel:0086-27-59701876 Fax:0086-27-59701879

Wuhan Dachu Hexing Technology Co.,Ltd E-mail:info@wohingwater.com Web: www.wohingwater.com Add: Building 3, District 5, Wuhan University Science Park, China

Technical Data Sheet

Dodecyl Benzene Sulfonic Acid Calcium CABS CAS No. 26264-06-2



Product Description

- Yellow to brown yellow clear viscous liquid.
- Soluble in organic solvents such as methanol, toluene and xylene etc.
- It is lipophilic composition in agricultural emulsifier. It can compound mixed agricultural emulsifier with many kinds of non-ion surface active agents.



wohingwater.com Tel:0086-27-59701876 Fax:0086-27-59701879 Wuhan Dachu Hexing Technology Co.,Ltd E-mail:info@wohingwater.com Web: www.wohingwater.com Add: Building 3, District 5, Wuhan University Science Park, China

Specifications:

Product Name	Туре	Active Ingredient %	Water Percentage	PH value	Major Solvent	Remarks	
Aqueous calcium salt	506	60±1	≤7	5~7	Methanol		
	507	70±2	≤7	5~7	Methanol		
Anhydrous	505 <i>A</i>	50±2	≤0.5	5~7	Alkane		
Calcium Salt	505L	50±2	≤0.5	5~7	Arene		
(Anhydrous Pesticide Emulsifier 500#)	506X	60±2	≤0.8	5~7	Octanol	Active ingredient percentage, water percentage and solvent can be custom made according to clients' requirement.	
	507L	70±4	≤0.5	5~7	Arene		
500#)	507B	70±2	≤0.5	5~7	Tarketanak	npound solvent	
					'		
	507 <i>C</i>	70±2	≤0.5	5~7	Methanol		
	507P	70±2	≤0.7	5~7	Isobutanol		

Usage

- Dodecyl Benzene Sulfonic Acid Calcium can compound with many kinds of non-ionic surface active agents to make mixed agricultural emulsifier.;
- It can be used to formulate pesticide, fungicide and herbicide. Caclium dodecyl benzene sulfonate is used as surfactants or agrochemical emulsifiers.
- It's widely used to formulate pesticide emulsifier for organic phosphorus and organochlorine products.

Packing and Storage

- Packed in 200KG iron drum. As per specific customer needs(available in bulk & small volume), the product can be made available with customized packing.
- Stored in dry and droughty place. Quality guaranteed period: 1 year.

Transport Information

DOT Classification: Not a DOT material

Note: The information and recommendations in this publication are to the best of our knowledge reliable. However, nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purpose. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed.