

Quzhou Quhua Zhongxing Refrigeration Technology Co., Ltd

Material Safety Data Sheet

1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION

Product Name R22
Chemical formula CH Cl F₂
Trade Name R22
Colour Coding Cornflower Blue(F.29)body with a Lime Green shoulder and guard.
Valve Neriki U6-5/8 inch BSP right hand male.
Company identification Quzhou Quhua Zhongxing Refrigeration Technology Co.,Ltd
No866 Quhua Road,
QuZhou ZheJiang China
Tel.No:(0570) 8886618
Fax.No: (0570) 2844010

2 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name: Chlorodifluoromethane
Chemical Family Chlorofluorocarbon
Cas No. 75-45-6
UN No. 1018
ERG No. 126
Hazchem Waring 2C non-flammable gas

3 HAZARDS IDENTIFICATION

Main Hazards All cylinders are portable gas contains, and must be regarded as pressure vessels at all times. R22 does not support life. It can act as a simple asphyxiant by diluting the concentration of oxygen in air to below the levels necessary to support life.

Adverse Health effects Contains a liquefied gas. Contact with liquid may cause frostbite and injury to the cornea.

Chemical hazards Heating will cause a rise in pressure with a risk of bursting. On combustion, toxic gases are released.

Biological hazards Contact with the liquid phase could cause freeze burns.

4 FIRST AID MEASURES

Prompt medical attention is mandatory in all cases of overexposure to vapourised R22. Rescue personnel should be equipped with self-contained breathing apparatus. Conscious persons should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be removed to an uncontaminated area and given mouth-to-mouth resuscitation and supplemental oxygen. The use of adrenaline or similar drugs should be avoided.

Eye contact (Vapour) No known effect.
(Liquid) Immediately flush with large quantities of tepid water, or with sterile saline solution. Seek medical attention.

Skin contact (Vapour) No known effect.
(Liquid) In case of frostbite from contact with liquid R22, place the frost-bitten part in warm water, about 40-42°C. If warm water is not available, or is impractical to use, wrap the affected part gently in blankets. Encourage the patient to exercise the affected part whilst it is being warmed. Do not remove clothing while frosted.

Ingestion Provided the patient is conscious, wash out the mouth with water, and give 200-300 ml to drink. Obtain immediate medical attention.

5 FIRE FIGHTING MEASURES

Extinguishing media As R22 is non-flammable, it will not contribute to the fire, but could help with the extinguishing by reducing the oxygen content of the air by dilution to below the level to support combustion. If possible, shut off the source of R22. Evacuate area. All cylinders should be removed from the vicinity of the fire. Cylinders that cannot be removed should be cooled with water from a safe distance. Cylinders which have been exposed to excessive heat should be clearly identified for inspection. CONTACT WITH OUR COMPANY.

Specific hazards. Pressurised container. On heating there is a risk of bursting due to internal pressure build-up not flammable. However, it may present a risk in the event of fire. Toxic vapours (Halogen compounds) are released. Vapour/air mixture may be flammable under specific conditions.

Protective Clothing Self-contained breathing apparatus. Safety gloves and shoes, or boots, should be worn when handling cylinders.

Environmental Care should be taken when entering a

Precautions potentially oxygen-deficient environment. If possible, ventilate the affected area.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions. Do not enter any areas where R22 has been spilled unless tests have shown that it is safe to do so.

Environmental Precautions Prevent the product from spreading into the environment. Contain the spilled material by bunding.

Small spills Shut off source of the R22. Ventilate the area.

Large spills Evacuate the area. Shut off the source of the spill if this can be done without risk. Restrict access to the area until completion of the clean-up procedure. Ventilate the area using forced-draught if necessary.

7 HANDLING AND STORAGE

Do not allow cylinders to slide or come in to into contact with sharp edges. R22 cylinders should be stacked vertically at all times, and should be firmly secured in order to prevent them from being knocked over. Use a "first in – first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Keep out of reach of children.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational As R22 is a simple asphyxiant, avoid any

Exposure hazards areas where spillage has taken place. Only enter once testing has proved the atmosphere to be safe, and remember that the gas is heavier than air.

Engineering Engineering control measures are preferred

Control measures to reduce oxygen depleted atmospheres. General methods includes forced-draught ventilation, separate from other exhaust ventilation systems. Ensure that sufficient fresh air enters at, or near, floor level.

Personal protection Self- contained breathing apparatus should always be worn when entering area where oxygen depletion may have occurred. Safety goggles, gloves and shoes or boots should be worn when handling cylinders.

Skin No known effect

9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL DATA

Chemical Symbol	CHCIF2
Molecular Weight	86,47
Boiling point@101,325kPa	-40,8°C
Density(saturated vapour)at boiling point	
Vapour pressure@21°C	1040kPa
Ozone depletion potential	0,55
Colour	Colourless
Taste	Not applicable
Odour	Slightly ethereal

10 TABILITY AND REACTIVITY

Conditions to avoid	Never use cylinders as rollers or supports, or for any other purpose than the storing of R22. Never expose the cylinders to excessive heat, as this may cause sufficient build-up of pressure to rupture the cylinders.
Incompatible materials	Since the performance of plastic materials affected by polymer variations, compounding agents, fillers, and moulding processes, verify compatibility using actual fabricated parts under end-use conditions is advised. The effects on specific elastomers depend on the nature of the polymer, the compounding formulation used and the curing of vulcanizing conditions. Actual samples should be tested under end-use conditions before specifying elastomers for critical components.
Hazardous Decomposition Produce	R22 vapours will decompose when exposed to high temperatures from flames or electric resistance heaters. Decomposition may produce toxic and irritating compounds, such as hydrogen fluoride.

11 TOXICOLOGICAL INFORMATION

Acute Toxicity(TWA 8+12 hr)	1000ppm
Skin & eye contact	No known effect
Carcinogenicity	No known effect
Mutagenicity	No known effect
Reproductive Hazards	No known effect

(For further information see Section 3. Adverse health effects)

12 ECOLOGICAL INFORMATION

Environmental	Dangerous to the ozone layer.
----------------------	-------------------------------

13 DISPOSAL CONSIDERATIONS

Disposal Methods	Do not allow the product to be released into the environment. Consult the manufacturer of supplier for information regarding recovery and recycling of product.
-------------------------	---

14 TRANSPORT INFORMATION**ROAD TRANSPORTATION**

UN No.	1018
ERG No.	126
Hazchem wording	2 C Non-flammable gas

SEA TRANSPORTATION

IMDG	1018
Class	2.2
Label	Non-flammable gas

AIR TRANSPORTATION

ICAO/IATA Code	1018
Class	2.2
Packaging instructions	
- Cargo	200
-Passenger	200
Maximum quantity allowed	
- Cargo	150kg
-Passenger	75kg

15 REGULATORY INFORMATION

EEC Hazard class	Non-flammable gas
-------------------------	-------------------

Risk phrases	R20 Harmful by inhalation R34 Cause burns. R44 Risk of explosion if heated under confinement. R59 Dangerous for the ozone layer
---------------------	--

Safety phrases	S2 Keep out of reach of children S9 Keep container in a well-ventilated place S15 Keep away from heat S37 Wear suitable gloves
-----------------------	---



S38 In case of insufficient ventilation, wear suitable respiratory equipment.

S51 Use only in well ventilated areas

National legislation None

Refer to SABS 0265 for explanation of thr above.

16 OTHER INFORMATION

All the constituents of this preparation are registered in the EINECS inventory. All the components of this preparation are registered in the TSCA inventory.

17 EXCLUSION OF LIABILITY

Information contained in this publication is accurate at the date of publication. The company does not accept liability arising from the use of this information, or the use, application, adaptation or process of any products described herein.