

SHIJIAZHANG CHENSHI IMPORT AND EXPORT CO.,LTD. NO.122 QILIAN STREET, GAOXIN DISTRICT, SHIJIAZAHUNG CITY, HEBEI, CHINA Tell: 0086 311 85252218 Fax : 0086 311 85831105

TDS of Barium Sulphate Precipitated

Description: Produce barium sulfate by processing and purifying barite.

Typical properties:

Resistant to acids and alkalis Insoluble in water and organic solvents An inert product which is lightfast and weather-resistant Colour-neutral, due to its low refractive index Extremely narrow particle- size range for high gloss specifications Extremely good wettability due to low specific surface area Low abrasion during processing, due to low Mohs hardness

Technical Data Sheet

Density	4.5 min
Oil absorption g /100g	13
BaSO ₄	98.5
Fe ₂ O ₃	0.004max
D50 um	0.5-0.7
Al ₂ O ₃	0.01max
Silicate	0.01max
Heavy metal	0.01max
Salt soluble	0.2max
Moisture	0.2max
L.O.I	0.5max
Whiteness	98min

Applications:

Paint and coating	Paper making
Ink	Plastic
Rubber	Battery

Packing: 25kg/bag or follow customer's design.

Storage: Keep the product in dry and closed rooms at normal temperature and air

humidity. To achieve best possible results, we recommend storage under the conditions stated above and use within 24 months from delivery.